NSN 5310-01-276-1652

Push On Nut - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-01-276-1652

| Material Thickness: |
|---|
| Between 0.036 inches and 0.052 inches |
| Mating Member Diameter Accommodated: |
| Between 0.246 inches and 0.254 inches |
| Nut Style: |
| Push on |
| Nut Diameter: |
| Between 0.517 inches and 0.527 inches |
| Features Provided: |
| Casehardened |
| Material: |
| Steel comp 1060 or steel comp 1064 or steel comp 1065 or steel comp 1069 or steel comp 1070 or steel comp 1074 or steel comp 1075 |
| or steel comp 1078 or steel comp 1080 or steel comp 1084 or steel comp 1085 or steel comp 1086 or steel comp 1090 |
| Surface Treatment: |
| Zinc and chromate or phosphate zinc |
| Surface Treatment Specification: |
| 171, finish 1.9.5 military standard 1st treatment response or mil-p-16232, type z, class 4d military specification 2nd treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| A021a0 |
| Mil-std (military Standard): |
| Mil-p-16232 spec. |
| |
| |