

View Online at https://aerobasegroup.com/nsn/5310-01-278-9013

| Thread Cl | ass: |
|-------------|--|
| 3b | |
| Thread Di | rection: |
| Right-hand | |
| Lubricatio | n: |
| Soluble lut | pricant |
| Overall Le | ngth: |
| 72.000 inc | hes |
| Overall W | idth: |
| 0.710 inch | es |
| Nut Style: | |
| Gang char | nel, self locking |
| Channel S | ityle: |
| Straight ty | De |
| Assembly | height: |
| 0.536 inch | es |
| Nut Count | erbore Depth: |
| 0.250 inch | es nut |
| Nut Quant | ity: |
| 72 | |
| Thread Se | ries: |
| Unjf | |
| Thready C | tty Per Inch (tpi): |
| 24 | |
| Thread Siz | ze: |
| 0.312 inch | es |
| Material: | |
| Aluminum | alloy 7075 |
| Material S | pecification: |
| Qq-a-250/* | 13d federal specification single material response |
| Surface T | reatment: |
| Anodize | |
| Surface T | reatment Specification: |
| Mil-a-8625 | , type ii, class 1, plus 2 coats mms425 military specification single treatment response |
| Shelf Life: | |
| N/a | |
| Unit Of Me | easure: |
| | |
| Demilitari | zation: |
| No | |
| Fiig: | |
| A021a0 | |



Mil-std (military Standard):

Mil-a-8625 spec.