Blind Rivet Self-locking Nut - Page 1 of 2





Thread Class: 3b **Thread Direction: Right-hand** Head Style: Eliptical countersunk **Head Height:** 0.034 inches Locking Feature: Prevailing torque all metal design Head Major Diameter: Between 0.310 inches and 0.332 inches Head Minor Diameter: 0.257 inches Lubrication: Dry film lubricant Nut Style: Blind rivet w/smooth round shank Nut Diameter: Between 0.239 inches and 0.241 inches Nut Length: 1.061 inches Nut Grip Range: +0.280/+0.340 inches Shank End Type: Closed **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unif Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1900 inches Head Major Countersink Angle: Between 75.0 degrees and 77.0 degrees Head Minor Countersink Angle: Between 59.0 degrees and 61.0 degrees Material: Steel comp 304 or steel comp 305 **Material Specification:**

Qq-s-763 federal specification all material responses

NSN 5310-01-281-3399

Blind Rivet Self-locking Nut - Page 2 of 2



Surface Treatment:

Cadmium or chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Specification Data:

80205-nas1735 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A021a0