

View Online at <https://aerobasegroup.com/nsn/5310-01-283-2695>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Counterbore Diameter:

0.194 inches nut

Lubrication:

Dry film lubricant

Overall Length:

Between 2.926 inches and 2.946 inches

Overall Width:

0.416 inches

Nut Style:

A20 gang channel, self locking

Channel Style:

Straight type

Assemblyheight:

0.250 inches

Channel Height:

0.250 inches

Nut Spacing:

Between 1.490 inches and 1.510 inches

Nut Counterbore Depth:

0.062 inches nut

Tempurature Rating:

232.0 degrees celsius

Nut Quantity:

2

Thread Series:

Unjf

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

32

Hardness Rating:

49.0 rockwell c

Thread Size:

0.190 inches

Material:

Steel comp 1035 or steel comp 1040 or steel comp 1050 or steel comp 1042 or steel comp 4130 or steel comp 4340 or steel comp 8740 nut

Material Specification:

Qq-s-635, g10350 federal specification 1st material response or qq-s-635, g10400 federal specification 2nd material response or qq-s-635, g10350 federal specification 3rd material response or astm a29, g10420 assn standard 4th material response or astm a29, g41300 assn standard 5th material response or astm a29, g43400 assn standard 6th material response or astm a29, g87400 assn standard 7th material response nut

Surface Treatment:

Passivate channel

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses nut

Supplementary Features:

STKL-G7-2.0-IN.N

Specification Data:

96906-ms21064 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0