

View Online at <https://aerobasegroup.com/nsn/5310-01-286-0816>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Counterbore Diameter:

0.173 inches nut

Overall Height:

0.405 inches

Mounting Hole Diameter:

0.098 inches

Nut Style:

Plate (floating)

Nut Length:

0.840 inches

Nut Height:

0.221 inches

Plate Thickness:

0.030 inches

Plate Width:

0.443 inches

Nut Counterbore Depth:

0.070 inches nut

Nut Mounting Provision:

Straight holes

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.290 inches and 0.300 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.588 inches and 0.592 inches

Temperature Rating:

450.0 degrees fahrenheit

Thread Series:

Unjc

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Special Features:

Part is identical to nas1474c06 except with a high-reuse lubricant instead of silver plating on the nut component; use lubricant mil-I-8937 plus cetyl alcohol per mil-I-87132, type and grade optional to meet end item requirements

Material:

Iron alloy 660 shell

Material Specification:

Ams 5732 assn standard single material response nut

Surface Treatment:

Passivate shell

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shell

Specification Data:

80205-nas1474 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0