

View Online at <https://aerobasegroup.com/nsn/5310-01-286-5973>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Mounting Hole Diameter:**

Between 0.098 inches and 0.103 inches

**Nut Style:**

Plate

**Nut Length:**

1.051 inches

**Nut Height:**

Between 0.367 inches and 0.397 inches

**Plate Thickness:**

Between 0.020 inches and 0.032 inches

**Plate Width:**

0.422 inches

**Nut Mounting Provision:**

Straight holes

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

Between 0.339 inches and 0.349 inches

**Center To Center Distance Between Mounting Holes Along Length:**

0.312 inches

**Thread Series:**

Unjf

**Features Provided:**

Floating nut

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Material:**

Steel comp 302 cap or steel comp 303 cap or steel comp 304 cap or steel comp 305 cap or steel comp 309 cap or steel comp 310 cap or steel comp m3 cap or steel comp 316 cap or steel comp 317 cap or steel comp 321 cap or steel comp 323 cap or steel comp 324 cap or steel comp 347 cap or steel comp 348 cap or steel comp 384 cap or steel comp 385 cap

**Material Specification:**

Ams 5525 assn standard single material response shell

**Precious Material And Location:**

Nut and cap silver

**Precious Material:**

Silver

**Surface Treatment:**

Passivate shell

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response shell

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0