
NSN 5310-01-292-5343

Spline Self-locking Nut - Page 1 of 2





Thread Class:

3b

Thread Direction:

Right-hand

Pilot Diameter:

Between 0.264 inches and 0.270 inches

Pilot Length:

0.440 inches

Lubrication:

Dry film lubricant

Nut Style:

Spline (floating)

Nut Length:

Between 0.547 inches and 0.582 inches

Nut Height:

Between 0.658 inches and 0.688 inches

Width Across Flats:

0.390 inches

Thread Series:

Unjf

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

32

Hardness Rating:

Between 40.0 rockwell c and 50.0 rockwell c

Thread Size:

0.190 inches

Special Features:

Hardness rating applies to the bracket only; the nut has a 160 ksi min tensile strength

Material:

Steel comp 304 shell or steel comp 305 shell

Material Specification:

Qq-s-777 federal specification 1st material response nut or ams 5085 assn standard 2nd material response nut

Surface Treatment:

Passivate shell and cadmium shell

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

NSN 5310-01-292-5343

Spline Self-locking Nut - Page 2 of 2



Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-s-23195 spec.