NSN 5310-01-292-5346

Key Washer - Page 1 of 1



| view Online at https://aerobasegroup.com/nsn/5310-01-292-5346 | |
|--|-----|
| Hole Diameter: | |
| Between 0.380 inches and 0.390 inches | |
| Outside Diameter: | |
| Between 0.550 inches and 0.570 inches | |
| Internal Prebent Key Width: | |
| Between 0.077 inches and 0.087 inches | |
| Material Thickness: | |
| Between 0.058 inches and 0.068 inches | |
| Hardness Rating: | |
| Between 38.0 rockwell c and 45.0 rockwell c | |
| Distance From Key Center To Wire Hole Center: | |
| Between 0.108 inches and 0.138 inches | |
| Wire Hole Diameter: | |
| Between 0.057 inches and 0.067 inches | |
| Material: | |
| Steel comp 630 or steel comp xm-12 | |
| Material Specification: | |
| Ams 5343 assn standard 1st material response or ams 5659 assn standard 2nd material response | nse |
| Surface Treatment: | |
| Cadmium and chromate | |
| Surface Treatment Specification: | |
| Qq-p-416, type 2, class 2 federal specification single treatment response | |
| Style Designator: | |
| Internal prebent key | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A022b0 | |