NSN 5310-01-301-1796

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-301-1796 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Counterbore Diameter:** 0.254 inches first end Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** 0.791 inches **Nut Height:** 0.536 inches **Plate Thickness:** 0.125 inches Plate Width: 0.500 inches **Nut Counterbore Depth:** 0.250 inches first end and 0.260 inches first end **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center:** Between 0.276 inches and 0.287 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.560 inches and 0.564 inches **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Thready Qty Per Inch (tpi):

Unif **Features Provided:** Floating nut 28 **Thread Size:** 0.2500 inches

NSN 5310-01-301-1796

Plate Self-locking Nut - Page 2 of 2



NЛ	2	te	rı	2	

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

Material Specification:

Mil-s-5059 military specification all material responses shell

Surface Treatment:

Cadmium shell and chromate shell or passivate shell

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-s-5626 spec.