

View Online at <https://aerobasegroup.com/nsn/5310-01-303-8160>

**Hole Diameter:**

Between 0.390 inches and 0.395 inches

**Outside Diameter:**

Between 0.560 inches and 0.570 inches

**External Prebent Key Length:**

Between 0.140 inches and 0.150 inches

**External Tapered Key Width:**

Between 0.450 inches and 0.460 inches

**External Prebent Key Width:**

Between 0.140 inches and 0.145 inches

**Distance From Centerline To Inside Of Prebent Key:**

Between 0.365 inches and 0.375 inches

**Overall Distance Including Keys:**

0.972 inches

**Split Key Length:**

0.297 inches

**External Key Quantity:**

3

**Material Thickness:**

Between 0.028 inches and 0.036 inches

**Angle Between External Keys:**

Between 58.0 degrees and 62.0 degrees

**External Prebent Key Angle:**

Between 10.0 degrees and 20.0 degrees

**Material:**

Steel comp 321 or steel comp 347

**Material Specification:**

Ams 5510 assn standard 1st material response or ams 5512 assn standard 2nd material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35, type 1 federal specification single treatment response or qq-p-35, type 2 federal specification single treatment response or qq-p-35, type 3 federal specification single treatment response

**Style Designator:**

Key

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A022b0