## NSN 5310-01-303-8160

Key Washer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-01-303-8160 **Hole Diameter:** Between 0.390 inches and 0.395 inches **Outside Diameter:** Between 0.560 inches and 0.570 inches **External Prebent Key Length:** Between 0.140 inches and 0.150 inches **External Tapered Key Width:** Between 0.450 inches and 0.460 inches **External Prebent Key Width:** Between 0.140 inches and 0.145 inches **Distance From Centerline To Inside Of Prebent Key:** Between 0.365 inches and 0.375 inches **Overall Distance Including Keys:** 0.972 inches Split Key Length: 0.297 inches **External Key Quantity:** 3 **Material Thickness:** Between 0.028 inches and 0.036 inches **Angle Between External Keys:** Between 58.0 degrees and 62.0 degrees **External Prebent Key Angle:** Between 10.0 degrees and 20.0 degrees Material: Steel comp 321 or steel comp 347 **Material Specification:** Ams 5510 assn standard 1st material response or ams 5512 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35, type 1 federal specification single treatment response or qq-p-35, type 2 federal specification single treatment response or qq-p-35, type 3 federal specification single treatment response **Style Designator:** Key Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig:

No

A022b0