NSN 5310-01-304-8732

Flat Washer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-01-304-8732

Cross Sectional Shape: Rectangular Hole Diameter: Between 0.251 inches and 0.255 inches Edge Shape: Round Center Hole Shape: 1 round Thickness: Between 0.057 inches and 0.069 inches Overall Diameter: Between 0.460 inches and 0.470 inches Material: Iron alloy 660 or nickel alloy 718 Material Specification: Ams 5525 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5596 assn standard 2nd material response or ams 5597 assn standard 2nd material response Surface Treatment: Aluminum alloy Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	
Hole Diameter: Between 0.251 inches and 0.255 inches Edge Shape: Round Center Hole Shape: 1 round Thickness: Between 0.057 inches and 0.069 inches Overall Diameter: Between 0.460 inches and 0.470 inches Material: Iron alloy 660 or nickel alloy 718 Material Specification: Ams 5525 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5596 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5662 assn standard 2nd material response Surface Treatment: Aluminum alloy Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	ctional Shape:
Between 0.251 inches and 0.255 inches Edge Shape: Round Center Hole Shape: 1 round Thickness: Between 0.057 inches and 0.069 inches Overall Diameter: Between 0.460 inches and 0.470 inches Material: Iron alloy 660 or nickel alloy 718 Material Specification: Arms 5525 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5596 assn standard 2nd materias response or ams 5597 assn standard 2nd material response or ams 5662 assn standard 2nd material response Surface Treatment: Aluminum alloy Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	lar
Edge Shape: Round Center Hole Shape: 1 round Thickness: Between 0.057 inches and 0.069 inches Overall Diameter: Between 0.460 inches and 0.470 inches Material: Iron alloy 660 or nickel alloy 718 Material Specification: Ams 5525 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5596 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5596 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5662 assn standard 2nd material response Surface Treatment: Aluminum alloy Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	neter:
Center Hole Shape: 1 round Thickness: Between 0.057 inches and 0.069 inches Overall Diameter: Between 0.460 inches and 0.470 inches Material: Iron alloy 660 or nickel alloy 718 Material Specification: Ams 5525 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5596 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5596 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5662 assn standard 2nd material response Surface Treatment: Aluminum alloy Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	0.251 inches and 0.255 inches
Center Hole Shape: 1 round Thickness: Between 0.057 inches and 0.069 inches Overall Diameter: Between 0.460 inches and 0.470 inches Material: Iron alloy 660 or nickel alloy 718 Material Specification: Arms 5525 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5596 assn standard 2nd material response or ams 5597 assn standard 2nd material response Surface Treatment: Aluminum alloy Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	ipe:
Trickness: Between 0.057 inches and 0.069 inches Overall Diameter: Between 0.460 inches and 0.470 inches Material: Iron alloy 660 or nickel alloy 718 Material Specification: Ams 5525 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5596 assn standard 2nd material response or ams 5597 assn standard 2nd material response Surface Treatment: Aluminum alloy Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	
Thickness: Between 0.057 inches and 0.069 inches Overall Diameter: Between 0.460 inches and 0.470 inches Material: Iron alloy 660 or nickel alloy 718 Material Specification: Ams 5525 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5596 assn standard 2nd materias response or ams 5597 assn standard 2nd material response or ams 5662 assn standard 2nd material response Surface Treatment: Aluminum alloy Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	ole Shape:
Between 0.057 inches and 0.069 inches Overall Diameter: Between 0.460 inches and 0.470 inches Material: Iron alloy 660 or nickel alloy 718 Material Specification: Ams 5525 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5596 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5597 assn standard 2nd material response Surface Treatment: Aluminum alloy Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	
Overall Diameter: Between 0.460 inches and 0.470 inches Material: Iron alloy 660 or nickel alloy 718 Material Specification: Ams 5525 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5596 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5597 assn standard 2nd material response Surface Treatment: Aluminum alloy Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	s:
Between 0.460 inches and 0.470 inches Material: Iron alloy 660 or nickel alloy 718 Material Specification: Ams 5525 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5596 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5597 assn standard 2nd material response Surface Treatment: Aluminum alloy Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	0.057 inches and 0.069 inches
Material: Iron alloy 660 or nickel alloy 718 Material Specification: Ams 5525 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5596 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5662 assn standard 2nd material response Surface Treatment: Aluminum alloy Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	iameter:
Material Specification: Ams 5525 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5596 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5662 assn standard 2nd material response Surface Treatment: Aluminum alloy Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	0.460 inches and 0.470 inches
Material Specification: Ams 5525 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5596 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5662 assn standard 2nd material response Surface Treatment: Aluminum alloy Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	
Ams 5525 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5596 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5662 assn standard 2nd material response Surface Treatment: Aluminum alloy Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	660 or nickel alloy 718
response or ams 5597 assn standard 2nd material response or ams 5662 assn standard 2nd material response Surface Treatment: Aluminum alloy Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	Specification:
Surface Treatment: Aluminum alloy Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5596 assn standard 2nd material
Aluminum alloy Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	or ams 5597 assn standard 2nd material response or ams 5662 assn standard 2nd material response
Surface Treatment Specification: Nas 4006 assn standard single treatment response Shelf Life: N/a	reatment:
Nas 4006 assn standard single treatment response Shelf Life: N/a	alloy
Shelf Life: N/a	reatment Specification:
N/a	assn standard single treatment response
	ı:
Unit Of Measure:	easure:
-	
Demilitarization:	ization:
No	
Fiig:	
A022b0	