

View Online at <https://aerobasegroup.com/nsn/5310-01-306-4857>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Counterbore Diameter:

0.194 inches nut

Lubrication:

Dry film lubricant

Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Nut Style:

Plate

Nut Length:

0.734 inches

Distance From Base To Center Of Aperture:

Between 0.205 inches and 0.215 inches

Nut Height:

0.250 inches

Plate Thickness:

Between 0.027 inches and 0.042 inches

Plate Width:

0.415 inches

Nut Counterbore Depth:

0.062 inches nut

Nut Mounting Provision:

Straight holes

Mounting Hole Arrangement Style:

2 holes

Distance From Mounting Hole Center To Base:

Between 0.370 inches and 0.380 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.217 inches and 0.221 inches

Temperature Rating:

450.0 degrees fahrenheit

Thread Series:

Unjf

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

32

Hardness Rating:

49.0 rockwell c

Thread Size:

0.190 inches

Material:

Steel comp 1035 or steel comp 1040 or steel comp 1050 or steel comp 4130 or steel comp 4340 or steel comp 8740

Material Specification:

Astm a29 assn standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0