## NSN 5310-01-310-1096

Plate Self-locking Nut - Page 1 of 2

**Thread Class:** 





## 3b **Thread Direction: Right-hand** Locking Feature: Prevailing torque all metal design Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches Nut Style: Plate Nut Length: Between 1.360 inches and 1.390 inches Nut Height: 0.333 inches **Plate Thickness:** Between 0.023 inches and 0.027 inches Plate Width: 0.865 inches **Nut Mounting Provision:** Straight holes Mounting Hole Arrangement Style: 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.557 inches and 0.567 inches Center To Center Distance Between Mounting Holes Along Length: Between 1.123 inches and 1.127 inches **Thread Series:** Unjf **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Special Features:** 17-7 ph cres, passivate channel and receptacle Material: Steel comp 631 spring **Material Specification:** Aisi assn standard all material responses nut

## NSN 5310-01-310-1096

Plate Self-locking Nut - Page 2 of 2



Surface Treatment:

Passivate spring

Surface Treatment Specification:

Qq-p-416, type 2 federal specification single treatment response nut

**Specification Data:** 

80205-nas1803 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A021a0