NSN 5310-01-310-3974

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-310-3974 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 0.098 inches and 0.113 inches **Nut Style:** Plate **Nut Length:** 1.051 inches **Nut Height:** Between 0.270 inches and 0.290 inches **Plate Thickness:** 0.029 inches Plate Width: 0.422 inches **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Mounting Hole Center To Base:** 0.637 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.310 inches and 0.314 inches **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unf **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches Material: Iron alloy 660 **Material Specification:**

Ams 5525 assn standard single material response or ams 5737 assn standard single material response

NSN 5310-01-310-3974

Plate Self-locking Nut - Page 2 of 2



$\overline{}$			-			
~ I	ırfa	ഫ	ırc	natr	nΔn	

Cadmium or cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification 1st treatment response or qq-p-416, type 2, cl 2 federal specification 2nd treatment response

Specification Data:

82918-bacn10ja manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A021a0