## NSN 5310-01-311-4614

Sleeve Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-311-4614

| Thread Class:   |
|---|
| 2b  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.630 inches  |
| Nut Style:  |
| Sleeve  |
| Nut Length:   |
| 1.620 inches  |
| Nut Width Across Flats:   |
| 1.000 inches  |
| Drilled Hole Diameter:  |
| Between 0.189 inches and 0.192 inches   |
| Hole Type And Quantity:   |
| 6 drilled   |
| Cross-sectional Shape:  |
| Hexagonal   |
| Tempurature Rating:   |
| Not rated   |
| Thread Series:  |
| Unf   |
| Thready Qty Per Inch (tpi):   |
| 18  |
| Hardness Rating:  |
| Not rated   |
| Thread Size:  |
| 0.625 inches  |
| Hole Configuration Style:   |
| Configuration a   |
| Countersink Angle:  |
| 90.0 degrees first end and 100.0 degrees first end                                |
| Special Features:   |
| Hole 0.565 in. Min and 0.578 in. Maximum diameter drilled through to threaded end |
| Material:   |
| Aluminum alloy 6061   |
| Material Specification:   |
| Qq-a-225/8, t6 federal specification single material response                     |
| Surface Treatment:  |
| Anodize   |
| Surface Treatment Specification:  |
| Mile 0005 type 0 of 0 military encodification single treatment response           |

Mil-a-8625, type 2, cl 2 military specification single treatment response

## NSN 5310-01-311-4614

Sleeve Nut - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A021a0

## Mil-std (military Standard):

Mil-a-8625 spec.

