

View Online at <https://aerobasegroup.com/nsn/5310-01-314-6761>

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Counterbore Diameter:**

5.5 millimeters nut

**Lubrication:**

Dry film lubricant

**Mounting Hole Diameter:**

Between 2.5 millimeters and 2.7 millimeters

**Nut Style:**

Plate

**Nut Length:**

27.4 millimeters

**Nut Height:**

Between 6.1 millimeters and 6.9 millimeters

**Plate Thickness:**

0.6 millimeters

**Plate Width:**

10.6 millimeters

**Nut Counterbore Depth:**

2.4 millimeters nut

**Nut Mounting Provision:**

Straight holes

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

9.5 millimeters

**Center To Center Distance Between Mounting Holes Along Length:**

8.0 millimeters

**Temperature Rating:**

235.0 degrees celsius

**Thread Series:**

Mj

**Features Provided:**

Floating nut

**Thread Size:**

5.0 millimeters

**Thread Pitch In Millimeters:**

0.80

**Thread Tolerance Class:**

4h6h internal

**Material:**

Steel

**Surface Treatment:**

Cadmium and chromate or cadmium and phosphate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification 1st treatment response or qq-p-416, type 3, cl 2 federal specification 2nd treatment response

**Specification Data:**

80205-na0073 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0