NSN 5310-01-317-8989

Barrel Self-locking Nut - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5310-01-317-8989 |
|---|
| Thread Class: |
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Lubrication: |
| Ory film lubricant |
| Nut Style: |
| Floating self-locking barrel |
| Nut Diameter: |
| Between 0.775 inches and 0.778 inches |
| Nut Length: |
| Between 0.865 inches and 0.875 inches |
| Barrel Height: |
| Between 0.460 inches and 0.470 inches |
| Nut Height: |
| 0.625 inches |
| End Application: |
| C-5b aircraft |
| Thread Series: |
| Jnjf |
| Гhready Qty Per Inch (tpi): |
| 20 |
| Thread Size: |
| 0.437 inches |
| Material: |
| Steel comp 8740 or steel comp 4340 |
| Material Specification: |
| Mil-s-6049 military specification 1st material response or ams 6322 assn standard 1st material response or mil-s-8844, class 1 military |
| specification 2nd material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 2 federal specification single treatment response |
| Specification Data: |
| 30205-nas577 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5310-01-317-8989

Barrel Self-locking Nut - Page 2 of 2



Fiig:

A021a0

Mil-std (military Standard):

Mil-s-6049 spec.