NSN 5310-01-319-4851

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-319-4851 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Counterbore Diameter:** 0.257 inches shell Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** 0.762 inches **Nut Height:** 0.285 inches **Plate Thickness:** 0.030 inches **Nut Counterbore Depth:** 0.062 inches nut and 0.077 inches nut **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.339 inches and 0.349 inches **Thread Series:** Unif **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches Material: Iron alloy 660 **Material Specification:**

Ams 5525 assn standard single material response or ams 5731 assn standard single material response or ams 5732 assn standard single

Surface Treatment:

material response or ams 5737 assn standard single material response

Passivate

NSN 5310-01-319-4851

Plate Self-locking Nut - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Test Data Document:

81349-mil-i-17214 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf	Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A021a0