

View Online at <https://aerobasegroup.com/nsn/5310-01-320-5920>

**Hole Diameter:**

Between 0.314 inches and 0.318 inches

**Outside Diameter:**

Between 0.575 inches and 0.585 inches

**Recess Diameter:**

Between 0.386 inches and 0.396 inches

**Material Thickness:**

Between 0.057 inches and 0.069 inches

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Recess Angle:**

90.0 degrees

**Material:**

Iron alloy 660 or nickel alloy 718

**Material Specification:**

Ams 5525 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5596 assn standard 2nd material response or ams 5597 assn standard 2nd material response or ams 5662 assn standard 2nd material response

**Surface Treatment:**

Aluminum alloy

**Surface Treatment Specification:**

Ams 4006 assn standard single treatment response

**Style Designator:**

15 recessed

**Test Data Document:**

96906-mil-std-6866 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A022b0

**Mil-std (military Standard):**

Mil-std-6866 spec.