

View Online at <https://aerobasegroup.com/nsn/5310-01-321-2425>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Counterbore Diameter:

0.194 inches nut

Lubrication:

Dry film lubricant

Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Nut Style:

Plate

Nut Length:

1.051 inches

Nut Height:

0.220 inches

Plate Thickness:

Between 0.028 inches and 0.036 inches

Plate Width:

0.454 inches

Removable Nut Manufacturer Code:

15653

Nut Counterbore Depth:

0.070 inches nut

Nut Mounting Provision:

Straight holes

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.339 inches and 0.349 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.310 inches and 0.314 inches

Removable Nut Manufacturer Part Number:

F52892-3-1xn

Tempurature Rating:

450.0 degrees fahrenheit

Thread Series:

Unjf

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Material:

Stainless steel clip

Material Specification:

Ams 5525 assn standard single material response shell or ams 5731 assn standard single material response shell or ams 5732 assn standard single material response shell

Surface Treatment:

Passivate shell

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shell

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0