Hexagon Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-326-0537

Ba Thread Direction: Right-hand Locking Feature: Pravaling torque all metal design Lubrication: Dyr film tubricant Nut Style: Hexagon Nut Height: 0.578 inches With Across Flats: Betwen 1.427 inches and 1.440 inches Tempurature Rating: 450.0 degrees fahrenheit Thread Series: Unif Thread Suppersize 46.0 rockwell o Darres Status: 1.000 inches Countersink Angle: 88.0 degrees nut Bearing Surface Tisis: 1.200 inches Bang Surface Fisis: 1.201 inches Materia: Surface Treatment: Aus Soles ass standard single material response Surface Treatment: Qarp-416, type	
Firead Direction: Right-hand Locking Feature: Prevailing torque all metal design Lubrication: Dy film lubricant Hexagon Nut Height: 0.578 inches Width Across Flats: Between 1.427 inches and 1.440 inches Tempurature Rating: 450.0 degrees fahrenheit Thread Stries: Unif Hardenss Rating: 46.0 rockwell c Thread Size: 1.000 inches Paring Surface Type: Charlered Finish: 8.0 degrees nut Bearing Surface Type: Charlered ruse fainse: 125.0 microinches Bearing Surface Type: Charlered ruse fainse: 125.0 microinches Material Stel comp 1050 Material Cadmium and chromate Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium and chromate Surface Treatment Supecification single t	Thread Class:
Right-hand Locking Feature: Prevailing torque all metal design Lubrication: Dy film lubricant Mutsyle: Hexagon Nut Height: 0.578 inches Width Across Flats: Between 1.427 inches and 1.440 inches Tempurature Rating: 450.0 degrees fahrenheit Thread Series: Unif Hardness Rating: 46.0 rockwell c Thread Size: 1.000 inches Bearing Surface Finish: 1.000 inches Bearing Surface Finish: 12.5.0 microinches Bearing Surface Finish: 12.5.0 microinches Bearing Surface Finish: 12.5.0 microinches Material Surface Treatment: Cadmium and chromate Surface Treatment Sectification Auge-the, type 2, cl 2 federal specification single treatment response Surface Treatment Sectification	
Locking Feature: Prevailing torque all metal design Lubrication: Dy film lubricant Mut Style: Hexagon Nut Height: 0.578 inches Width Across Flats: Between 1.427 inches and 1.440 inches Tempurature Rating: 450.0 degrees fahrenheit Thread Series: Urif Partness Rating: 46.0 rockwell c Thread Size: 1.000 inches Bearing Surface Type: Chamfered or washer faced Bearing Surface Type: 125.0 microinches Material Specification: Asolo des ass astandard single material response Surface Treatment Specification: Cadmium and chromate Surface Treatment Specification: Cadmium and chromate Surface Treatment Specification: Cadmium and chromate Surface Treatment Specification Cadmium and chromate Surface Treatment Specification Cadmium and chromate Surface Treatment Specification: Cadmium and chromate	
Prevailing torque all metal design Lubrication: Dyr film tubricant Nut Style: Hexagon Nut Height: 0.578 inches Width Across Flats: Between 1.427 inches and 1.440 inches Torparature Rating: 450.0 degrees fahrenheit Thread Series: Unif Thread Series: Unif Atoross Rating: 450.0 degrees fahrenheit Thread Series: Unif Bernens Rating: 450.0 cockwell c Thread Series: 1.000 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material Seel comp 1050 Material Specification: Ams 5085 asen standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Cadmium and chromate Surface Treatment Specification <td< th=""><th>-</th></td<>	-
Lubrication: Dry film lubricant Nut Style: Hexagon Nut Height: 0.578 inches With Across Flats: Between 1.427 inches and 1.440 inches Tempurature Rating: 450.0 degrees fahrenheit Thread Series: Unjf Thready Qty Per Inch (tpi): 12 Hardness Rating: 46.0 rockwell c Thread Size: 1.000 inches Bearing Surface Type: Countersink Angle: 88.0 degrees nut Bearing Surface Type: 125.0 microinches Material: Stel comp 1050 Material: Surface Finish: Cadmium and chromate Surface Treatment Sepolification: Cadmium and chromate Surface Treatment Sepolification single treatment response Surface Treatment Sepolification: Natorial:	
Dry film tubricantNut Style:HexagonNut Height:0.578 inchesWidth Across Flats:Between 1.427 inches and 1.440 inchesTempurature Rating:450.0 degrees fahrenheitThread Series:UnifThready Qty Per Inch (tpi):12Hardness Rating:46.0 rockwell cThread Size:1.000 inchesCountersink Angle:88.0 degrees nutBearing Surface Type:Chamfered or washer facedBearing Surface Finish:12.5 on incroinchesMaterialSteel comp 1050MaterialCadmium and chromateSurface Treatment:Cadmium and chromateSurface TreatmentCadmum and chromateSurface Treatment:Q-p-416, type 2, cl 2 federal specification single treatment responseSuff Life:N/a	
Nut Style:HexagonNut Height:0.578 inchesWidth Across Flats:Between 1.427 inches and 1.440 inchesTempurature Rating:450.0 degrees fahrenheitThread Series:UnifThread Series:UnifHardness Rating:46.0 rockwell cThread Size:1.000 inchesCountersink Angle:88.0 degrees nutBearing Surface Type:Chamfered or washer facedBearing Surface Tinish:12.0 incinchesSteel comp 1050MaterialSteel comp 1050MaterialCandi and single material responseSurface Treatment:Cardinum and chromateSurface Treatment:Cardent Surface Type:Chard Size:12.000 inchesDescription:Chard Freatment:13.000 inchesCountersink Angle:Bearing Surface Type:Chard Streater Finish:12.0 microinchesMaterialSteel comp 1050MaterialCardinum and chromateCardinum and chromateSurface Treatment:Cardinum and chromateSurface Treatment Specification single treatment responseShelf Life:NaNaSurface Treatment Specification single treatment responseShelf Life:NaNaSteel Comp 1050Steel Comp 1050Steel Comp 1050Steel Comp 1050Steel	
Hexagon Nut Height: 0.578 inches Width Across Flats: Between 1.427 inches and 1.440 inches Tempurature Rating: 450.0 degrees fahrenheit Thread Series: Unif Thready Qty Per Inch (tpl): 12 Hardness Rating: 45.0 rockwell c Thread Size: 1000 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material Specification: Ans 5085 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification single treatment response Surface Treatment Specification single	Dry film lubricant
Nut Height:0.578 inchesWidth Across Flats:Between 1.427 inches and 1.440 inchesTempurature Rating:450.0 degrees fahrenheitThread Series:UnjfThready Qty Per Inch (tpi):12Hardness Rating:46.0 rockwell cThread Size:1.000 inchesCountersink Angle:88.0 degrees nutBearing Surface Type:Chamfered or washer facedBearing Surface Tinish:125.0 microinchesMaterialSteel comp 1050MaterialSurface Treatment:Cadmium and chromateSurface TreatmentQ-q-416, type 2, cl 2 federal specification single treatment responseNatNat	Nut Style:
0.578 inchesWidth Across Flats:Between 1.427 inches and 1.440 inches Tempurature Rating: 450.0 degrees fahrenheitThread Series:UnifThready Qty Per Inch (tpi):12Hardness Rating:46.0 rockwell cThread Size:1.000 inchesCountersink Angle:88.0 degrees nutBearing Surface Type:Chamfered or washer facedBearing Surface Finish:125.0 microinchesMaterial:Steel comp 1050Material Specification:Arnos Sas standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification single treatment responseSurface Treatment SpecificationNa	Hexagon
Width Across Flats:Between 1.427 inches and 1.440 inches Tempurature Rating: 450.0 degrees fahrenheitThread Series:UnjfThready Qty Per Inch (tpi):12Hardness Rating:46.0 rockwell cThread Size:1.000 inchesCountersink Angle:88.0 degrees nutBearing Surface Finish:12.5 microinchesMaterial:Steel comp 1050Material:Steel comp 1050Surface Treatment:Cadmium and chromateSurface Treatment:Cadmium and chromateSurface Treatment Specification:Aug-p-416, type 2, cl 2 federal specification single treatment responseSurface INa	Nut Height:
Between 1.427 inches and 1.440 inches Tempurature Rating: 450.0 degrees fahrenheit Thread Series: Unjf Thready Oty Per Inch (tpi): 12 Hardness Rating: 46.0 rockwell c Thread Size: 1.000 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 12.5.0 microinches Material: Steel comp 1050 Material: Cadmium and chromate Surface Treatment Specification: Q-p-416, type 2, cl 2 federal specification single treatment response Surface Treatment	0.578 inches
Tempurature Rating:450.0 degrees fahrenheit450.0 degrees fahrenheitFhread Series:UnjfThready Oty Per Inch (tpi):12Hardness Rating:45.0 rockwell cThread Size:1.000 inchesCountersink Angle:88.0 degrees nutBearing Surface Type:Chamfered or washer facedBearing Surface Finish:125.0 microinchesMaterial:Steel comp 1050Material Specification:Ams 5085 assn standard single material responseSurface TreatmentQ-p-416, type 2, cl 2 federal specification single treatment responseNati	Width Across Flats:
450.0 degrees fahrenheit Thread Series: Unjf Thready Qty Per Inch (tpi): 12 Hardness Rating: 46.0 rockwell c Thread Size: 1.000 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Steel comp 1050 Material Specification: Ams 5085 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification single treatment response Shelf Life: N/a	Between 1.427 inches and 1.440 inches
Thread Series: Unif Thready Qty Per Inch (tpi): 12 Hardness Rating: 46.0 rockwell c Thread Size: 1.000 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Steel comp 1050 Material Specification: Ams 5085 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification single treatment response Surface Treatment Specification single tr	Tempurature Rating:
Unjf Thready Qty Per Inch (tpi): 12 Hardness Rating: 46.0 rockwell c Thread Size: 1.000 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Steel comp 1050 Material Specification: Ams 5085 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response Shelf Life: N/a	450.0 degrees fahrenheit
Thready Qty Per Inch (tpi): 12 Hardness Rating: 46.0 rockwell c Thread Size: 1.000 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Steel comp 1050 Material Specification: Ams 5085 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response Shelf Life: N/a	Thread Series:
12 Hardness Rating: 46.0 rockwell c Fhread Size: 1.000 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: 125.0 microinches Material: Steel comp 1050 Material Specification: Ams 5085 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification single treatment response Surface Treatment Specification: Ary-416, type 2, cl 2 federal specification single treatment response	Unjf
Hardness Rating:46.0 rockwell cFhread Size:1.000 inchesCountersink Angle:88.0 degrees nutBearing Surface Type:Chamfered or washer facedBearing Surface Finish:125.0 microinchesMaterial:Steel comp 1050Material Specification:Ams 5085 assn standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment SpecificationsQr-p-416, type 2, cl 2 federal specification single treatment responseN/a	Thready Qty Per Inch (tpi):
46.0 rockwell c Thread Size: 1.000 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Steel comp 1050 Material Specification: Ams 5085 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification single treatment response Surface Treatment Specification single treatment response Shelf Life: N/a	12
Thread Size:1.000 inchesCountersink Angle:88.0 degrees nutBearing Surface Type:Chamfered or washer facedBearing Surface Finish:125.0 microinchesMaterial:Steel comp 1050Material Specification:Ams 5085 assn standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qr-p-416, type 2, cl 2 federal specification single treatment responseShelf Life:N/a	Hardness Rating:
1.000 inches Countersink Angle: 88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material Steel comp 1050 Material Specification: Ams 5085 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification single treatment response Sheff Life: N/a	46.0 rockwell c
Countersink Angle:88.0 degrees nutBearing Surface Type:Chamfered or washer facedBearing Surface Finish:125.0 microinchesMaterial:Steel comp 1050Material Specification:Ams 5085 assn standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qr-p-416, type 2, cl 2 federal specification single treatment responseShelf Life:N/a	Thread Size:
88.0 degrees nut Bearing Surface Type: Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Steel comp 1050 Material Specification: Ams 5085 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response Shelf Life: N/a	1.000 inches
Bearing Surface Type:Chamfered or washer facedBearing Surface Finish:125.0 microinchesMaterial:Steel comp 1050Material Specification:Ams 5085 assn standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, type 2, cl 2 federal specification single treatment responseShelf Life:N/a	Countersink Angle:
Chamfered or washer faced Bearing Surface Finish: 125.0 microinches Material: Steel comp 1050 Material Specification: Ams 5085 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response Shelf Life: N/a	88.0 degrees nut
Bearing Surface Finish:125.0 microinchesMaterial:Steel comp 1050Material Specification:Ams 5085 assn standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, type 2, cl 2 federal specification single treatment responseShelf Life:N/a	Bearing Surface Type:
125.0 microinches Material: Steel comp 1050 Material Specification: Ams 5085 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response Shelf Life: N/a	Chamfered or washer faced
Material:Steel comp 1050Material Specification:Ams 5085 assn standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, type 2, cl 2 federal specification single treatment responseShelf Life:N/a	Bearing Surface Finish:
Steel comp 1050 Material Specification: Ams 5085 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response Shelf Life: N/a	125.0 microinches
Material Specification:Ams 5085 assn standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, type 2, cl 2 federal specification single treatment responseShelf Life:N/a	Material:
Ams 5085 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response Shelf Life: N/a	Steel comp 1050
Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response Shelf Life: N/a	Material Specification:
Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response Shelf Life: N/a	Ams 5085 assn standard single material response
Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response Shelf Life: N/a	Surface Treatment:
Qq-p-416, type 2, cl 2 federal specification single treatment response Shelf Life: N/a	Cadmium and chromate
Shelf Life: N/a	Surface Treatment Specification:
N/a	Qq-p-416, type 2, cl 2 federal specification single treatment response
	Shelf Life:
	N/a
Unit Of Measure:	Unit Of Measure:

--

NSN 5310-01-326-0537

Hexagon Self-locking Nut - Page 2 of 2

Demilitarization:

No

Fiig:

A021a0

