## NSN 5310-01-327-5704

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-327-5704 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** 1.051 inches **Nut Height:** 0.299 inches **Plate Thickness:** Between 0.028 inches and 0.036 inches Plate Width: 0.462 inches **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.339 inches and 0.349 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.310 inches and 0.314 inches **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unif **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Special Features:** 

Material:

Stainless steel clip

Nut coated with blue dye color

## NSN 5310-01-327-5704

Plate Self-locking Nut - Page 2 of 2



## **Material Specification:**

Ams 5525 assn standard single material response shell or ams 5731 assn standard single material response shell or ams 5732 assn standard single material response shell

**Surface Treatment:** 

Passivate shell

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response shell

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A021a0