

View Online at <https://aerobasegroup.com/nsn/5310-01-330-7124>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Counterbore Diameter:

0.300 inches nut

Lubrication:

Dry film lubricant

Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Nut Style:

Plate

Nut Length:

1.038 inches

Nut Height:

0.400 inches

Plate Thickness:

0.032 inches

Nut Counterbore Depth:

0.188 inches nut

Nut Mounting Provision:

Straight holes

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.495 inches and 0.505 inches

Thread Series:

Unjf

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Special Features:

Nut dry film lubricant per mil-I-8937, "kal-gard" type "fa", "kaylube" or "everlube" only.

Material:

Iron alloy 660

Material Specification:

Ams 5525 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A021a0