## NSN 5310-01-330-7125

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-330-7125 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Counterbore Diameter:** 0.195 inches base and 0.200 inches base Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 0.093 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** 1.375 inches **Nut Height:** 0.850 inches **Plate Thickness:** Between 0.023 inches and 0.027 inches Plate Width: 0.865 inches **Nut Counterbore Depth:** 0.843 inches base and 0.853 inches base **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center:** Between 0.557 inches and 0.567 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 1.123 inches and 1.127 inches **Thread Series:** Unjf **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Special Features:** 

Three shims, cres, 0.010 in. Thk, w/peel tabs, bonded to base; nut shank protrudes 0.140 in. Min, 0.160 in. Maximum fm base

## NSN 5310-01-330-7125

Plate Self-locking Nut - Page 2 of 2



Steel comp 631 spring
Material Specification:
Ams 5731 assn standard single material response nut or ams 5732 assn standard single material response nut or ams 5525 assn standard

**Surface Treatment:** 

single material response nut

Passivate

Material:

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A021a0