

View Online at <https://aerobasegroup.com/nsn/5310-01-330-7601>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque with metallic insert

Counterbore Diameter:

0.196 inches base and 0.202 inches base

Lubrication:

Dry film lubricant

Mounting Hole Diameter:

Between 0.093 inches and 0.103 inches

Nut Style:

Plate

Nut Length:

1.100 inches

Distance From Base To Center Of Aperture:

Between 0.290 inches and 0.330 inches

Plate Thickness:

Between 0.040 inches and 0.060 inches

Plate Width:

1.570 inches

Nut Counterbore Depth:

0.680 inches base

Nut Mounting Provision:

Straight holes

Mounting Hole Arrangement Style:

2 holes

Center To Center Distance Between Mounting Holes Along Width:

Between 1.000 inches and 1.030 inches

Drilled Hole Diameter:

Between 0.063 inches and 0.070 inches

Hole Type And Quantity:

2 tapped

Tempurature Rating:

300.0 degrees fahrenheit

Thread Series:

Unf

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Hole Configuration Style:

Configuration f

Special Features:

Includes insert, ms21209f1-15l, shank end

Material:

Aluminum alloy 2014 nut

Material Specification:

Qq-a-367, t6 federal specification single material response nut

Surface Treatment:

Anodize nut or chromate nut

Surface Treatment Specification:

Mil-a-8625, type 1 military specification 1st treatment response nut or mil-c-5541 military specification 2nd treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.