NSN 5310-01-330-9807

Clinch Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-330-9807

| Thread Class: |
|---|
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Pilot Diameter: |
| Between 0.182 inches and 0.187 inches |
| Pilot Length: |
| Between 0.073 inches and 0.083 inches |
| Lubrication: |
| Dry film lubricant |
| Nut Style: |
| Clinch |
| Nut Diameter: |
| Between 0.235 inches and 0.265 inches |
| Nut Height: |
| Between 0.163 inches and 0.193 inches |
| Tempurature Rating: |
| 600.0 degrees fahrenheit |
| Thread Series: |
| Unjc |
| Thready Qty Per Inch (tpi): |
| 32 |
| Hardness Rating: |
| 90.0 rockwell c |
| Thread Size: |
| 0.138 inches |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5732 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5310-01-330-9807

Clinch Self-locking Nut - Page 2 of 2

Fiig: A021a0

Mil-std (military Standard):

Mil-n-45938 spec.

