NSN 5310-01-336-5339

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-336-5339 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Counterbore Diameter:** 0.194 inches nut Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** Between 0.752 inches and 0.772 inches **Nut Height:** Between 0.395 inches and 0.415 inches **Plate Thickness:** Between 0.020 inches and 0.040 inches **Nut Counterbore Depth:** 0.187 inches nut and 0.202 inches nut **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.339 inches and 0.349 inches Center To Center Distance Between Mounting Holes Along Width: Between 0.484 inches and 0.488 inches **Thread Series:** Unif **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 32 **Thread Size:**

0.190 inches

Material:

Iron alloy 660 first end

Material Specification:

Ams 5525 assn standard single material response first end or ams 5735 assn standard single material response first end or ams 5737 assn standard single material response first end

NSN 5310-01-336-5339

Plate Self-locking Nut - Page 2 of 2

A021a0



Surface Treatment:
Passivate first end
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response first end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: