

View Online at <https://aerobasegroup.com/nsn/5310-01-337-7025>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Counterbore Diameter:

0.184 inches nut and 0.204 inches nut

Lubrication:

Dry film lubricant

Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Nut Style:

Plate

Nut Length:

1.051 inches

Nut Height:

0.558 inches

Plate Thickness:

Between 0.028 inches and 0.036 inches

Plate Width:

Between 0.452 inches and 0.472 inches

Nut Counterbore Depth:

0.365 inches nut and 0.375 inches nut

Nut Mounting Provision:

Straight holes

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.495 inches and 0.505 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.310 inches and 0.314 inches

Thread Series:

Unf

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Material:

Iron alloy 660 shell

Material Specification:

Ams 5525 assn standard single material response shell or ams 5732 assn standard single material response shell or ams 5737 assn standard single material response shell

Surface Treatment:

Passivate shell

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shell

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0