

View Online at <https://aerobasegroup.com/nsn/5310-01-338-0443>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Counterbore Diameter:**

0.317 inches nut

**Lubrication:**

Dry film lubricant

**Mounting Hole Diameter:**

Between 0.130 inches and 0.145 inches

**Nut Style:**

Plate

**Nut Length:**

1.396 inches

**Nut Height:**

Between 0.363 inches and 0.383 inches

**Plate Thickness:**

0.035 inches

**Plate Width:**

0.641 inches

**Nut Counterbore Depth:**

0.062 inches nut

**Nut Mounting Provision:**

Straight holes

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

Between 0.495 inches and 0.505 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 0.310 inches and 0.314 inches

**Temperature Rating:**

450.0 degrees fahrenheit

**Thread Series:**

Unjf

**Features Provided:**

Floating nut

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.312 inches

**Special Features:**

Kalgard fa lubricant

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5525 assn standard single material response or ams 5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0