NSN 5310-01-339-1429



Plate Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-01-339-1429 **Thread Class: Thread Direction:** Right-hand **Locking Feature:** Prevailing torque with nonmetallic insert **Counterbore Diameter:** 0.290 inches nut Lubrication: Dry film lubricant **Overall Height:** 0.790 inches **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** 1.300 inches **Nut Height:** 0.380 inches **Plate Thickness:** 0.020 inches Plate Width: 0.670 inches **Nut Counterbore Depth:** 0.090 inches nut **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.495 inches and 0.505 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.998 inches and 1.002 inches **Tempurature Rating:** 250.0 degrees fahrenheit **Thread Series:** Unjf **Features Provided:**

Features Provided:
Floating nut
Thready Qty Per Inch (tpi):
28

NSN 5310-01-339-1429Plate Self-locking Nut - Page 2 of 2



| Thread Size: |
|---|
| 0.250 inches |
| Product Name: |
| Navy special project |
| Special Features: |
| Color seal black; lubricated kalgard fa |
| Material: |
| Rubber butadiene-acrylonitrile class nbr seal |
| Surface Treatment: |
| Passivate nut |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response nut |
| Specification Data: |
| 81205-bacn10jz manufacturers standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - - |
| Demilitarization: |
| No |
| Fiig: |
| A021a0 |
| |