

NSN 5310-01-339-5953 Gang Channel Self-locking Nut Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-01-339-5953 **Thread Class: Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Counterbore Diameter:** 0.194 inches first end Lubrication: Dry film lubricant **Overall Length:** 71.940 inches **Overall Width:** 0.474 inches **Nut Style:** Gang channel, self locking **Channel Style:** Straight type Assemblyheight: 0.491 inches **Channel Height:** 0.250 inches **Nut Spacing:** 1.100 inches **Nut Counterbore Depth:** 0.313 inches first end **Nut Quantity:** 64

Thread Series:

Unjf

**Features Provided:** 

Floating nut

Thready Qty Per Inch (tpi):

32

**Thread Size:** 

0.190 inches

**Special Features:** 

Channel matl alclad

Material:

Steel comp xm-28 clip or steel comp 302 clip

**Material Specification:** 

Ams 5688 assn standard 2nd material response clip

## NSN 5310-01-339-5953

Gang Channel Self-locking Nut Assembly - Page 2 of 2



	S	urfa	ace	Tr	ea	tm	en	t	
--	---	------	-----	----	----	----	----	---	--

Passivate clip

## **Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response nut

## **Test Data Document:**

81349-mil-n-25027 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

S				

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.