NSN 5310-01-339-6522

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-339-6522 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Counterbore Diameter:** 0.194 inches nut Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate (floating) **Nut Length:** 0.953 inches **Nut Height:** 0.478 inches **Plate Thickness:** 0.030 inches Plate Width: 0.410 inches **Nut Counterbore Depth:** 0.302 inches nut and 0.322 inches nut **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center:** Between 0.339 inches and 0.349 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.686 inches and 0.700 inches **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unif **Features Provided:** Floating nut Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

NSN 5310-01-339-6522

Plate Self-locking Nut - Page 2 of 2

Fiig: A021a0



Material:
Iron alloy 660
Material Specification:
Ams 5525 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, ty2, cl2 federal specification single treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No