

View Online at <https://aerobasegroup.com/nsn/5310-01-341-3127>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Lubrication:

Dry film lubricant

Nut Style:

Hexagon

Nut Height:

0.125 inches

Width Across Flats:

Between 0.243 inches and 0.251 inches

Tempurature Rating:

450.0 degrees fahrenheit

Thread Series:

Unc

Thready Qty Per Inch (tpi):

40

Hardness Rating:

Between 36.0 rockwell c and 44.0 rockwell c

Thread Size:

0.112 inches

Bearing Surface Type:

Flat

Special Features:

Lubrication mil-I-40610

Material:

Steel comp 8740 or steel comp 4340 or steel comp 4140

Material Specification:

Mil-s-6049 military specification 1st material response or ams 6322 assn standard 1st material response or mil-s-5000 military specification 2nd material response or ams 6378 assn standard 3rd material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A021a0

Mil-std (military Standard):

Mil-s-6049 spec.