
Blind Rivet Self-locking Nut - Page 1 of 2





**Thread Class:** 3b **Thread Direction: Right-hand** Head Style: Eliptical countersunk **Head Height:** 0.048 inches Locking Feature: Prevailing torque all metal design Head Major Diameter: Between 0.602 inches and 0.625 inches **Head Minor Diameter:** 0.5050 inches Lubrication: Dry film lubricant Nut Style: Blind rivet w/smooth round shank Nut Diameter: Between 0.469 inches and 0.471 inches Nut Length: Between 1.567 inches and 1.657 inches Nut Grip Range: +0.970/+1.000 inches Shank End Type: Closed **Thread Series:** Unjf Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches Head Major Countersink Angle: 76.0 degrees Head Minor Countersink Angle: 60.0 degrees Material: Steel comp 304 or steel comp 305 **Material Specification:** Qq-s-763, conda federal specification single material response Surface Treatment: Cadmium and chromate

## NSN 5310-01-341-3133

Blind Rivet Self-locking Nut - Page 2 of 2



## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Specification Data:**

80205-nas1734 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0