Hexagon Extended Washer Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-348-3572

3b Thread Direction: Right-hand Locking Feature: Prevailing torque all metal design Washer Outside Diameter: Between 0.585 inches and 0.595 inches
Right-hand Locking Feature: Prevailing torque all metal design Washer Outside Diameter: Between 0.585 inches and 0.595 inches
Locking Feature: Prevailing torque all metal design Washer Outside Diameter: Between 0.585 inches and 0.595 inches
Prevailing torque all metal design Washer Outside Diameter: Between 0.585 inches and 0.595 inches
Washer Outside Diameter: Between 0.585 inches and 0.595 inches
Between 0.585 inches and 0.595 inches
Counterbore Diameter:
0.250 inches first end and 0.254 inches first end
Lubrication:
Dry film lubricant
Overall Height:
Between 0.290 inches and 0.300 inches
Nut Style:
Hexagon
Washer Thickness:
Between 0.045 inches and 0.065 inches
Nut Counterbore Depth:
0.291 inches first end and 0.296 inches first end
Width Across Flats:
Between 0.305 inches and 0.316 inches
Tempurature Rating:
450.0 degrees fahrenheit
Thread Series:
Unjf
Thready Qty Per Inch (tpi):
28
Thread Size:
0.250 inches
Special Features:
Shank extending from washer end; length .218max, .214min; diameter .375 max, .371min
Material:
Iron alloy 660
Material Specification:
Ams 5735 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response

Shelf Life:

N/a

AeroBase Group

Unit Of Measure:

Demilitarization:

No

Fiig:

A021a0