
NSN 5310-01-348-7126

Plate Self-locking Nut - Page 1 of 2



Thread Class:

2b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Lubrication:

Dry film lubricant

Mounting Hole Diameter:

0.148 inches

Nut Style:

Plate

Nut Length:

Between 0.975 inches and 0.995 inches

Nut Height:

Between 2.380 inches and 2.420 inches

Plate Thickness:

Between 0.050 inches and 0.070 inches

Plate Width:

Between 0.386 inches and 0.406 inches

Nut Mounting Provision:

Straight holes

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.334 inches and 0.354 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.686 inches and 0.690 inches

Tempurature Rating:

250.0 degrees fahrenheit

Thread Series:

Unf

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Material:

Stainless steel locking insert

Material Specification:

Mil-a-12545 military specification single material response except insert

Surface Treatment:

Anodize except insert



NSN 5310-01-348-7126

Plate Self-locking Nut - Page 2 of 2



Surface Treatment Specification:

Mil-a-8625 military specification single treatment response except insert

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-12545 spec.