
Hexagon Extended Washer Self-locking Nut - Page 1 of 2



| Thread Class: |
|--|
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Washer Outside Diameter: |
| 0.363 inches |
| Counterbore Diameter: |
| 0.205 inches first end and 0.210 inches first end |
| Lubrication: |
| Dry film lubricant |
| Overall Height: |
| 0.280 inches |
| Nut Style: |
| Hexagon |
| Nut Counterbore Depth: |
| 0.102 inches first end and 0.112 inches first end |
| Width Across Flats: |
| Between 0.245 inches and 0.252 inches |
| Thread Series: |
| Unjf |
| Thready Qty Per Inch (tpi): |
| 32 |
| Hardness Rating: |
| Between 33.0 rockwell c and 44.0 rockwell c |
| Thread Size: |
| 0.190 inches |
| Material: |
| Stainless steel washer |
| Material Specification: |
| Qq-s-763 federal specification single material response washer |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |



NSN 5310-01-349-0837

Hexagon Extended Washer Self-locking Nut - Page 2 of 2

Fiig: A021a0

