NSN 5310-01-352-1158

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-352-1158

| Thread Class: |
|--|
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Lubrication: |
| Dry film lubricant |
| Nut Style: |
| Plate (floating) |
| Nut Length: |
| 0.948 inches |
| Nut Height: |
| 0.143 inches |
| Plate Thickness: |
| 0.047 inches |
| Plate Width: |
| Between 0.235 inches and 0.260 inches |
| Nut Mounting Provision: |
| Straight holes |
| Tempurature Rating: |
| 450.0 degrees fahrenheit |
| Thread Series: |
| Unjc |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.112 inches |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5525 assn standard single material response or ams 5737 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Specification Data: |
| 80205-nas1770 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5310-01-352-1158

Plate Self-locking Nut - Page 2 of 2



Demilitarization:

No

Fiig:

A021a0