

View Online at https://aerobasegroup.com/nsn/5310-01-352-7376

| View Online at https://aerobasegroup.com/nsn/3510-01-352-7370   |
|---|
| Thread Class:   |
| 3b  |
| Thread Direction:   |
| Right-hand  |
| Locking Feature:  |
| Prevailing torque all metal design  |
| Washer Outside Diameter:  |
| 1.000 inches  |
| Counterbore Diameter:   |
| 0.616 inches first end and 0.626 inches first end   |
| Lubrication:  |
| Dry film lubricant  |
| Overall Height:   |
| Between 0.583 inches and 0.603 inches   |
| Nut Style:  |
| Double hexagon  |
| Washer Thickness:   |
| Between 0.072 inches and 0.087 inches   |
| Width Across Flats:   |
| Between 0.616 inches and 0.627 inches   |
| Thread Series:  |
| Unjf  |
| Thready Qty Per Inch (tpi):   |
| 20  |
| Thread Size:  |
| 0.500 inches  |
| Material:   |
| Iron alloy 660  |
| Material Specification:   |
| Ams 5737 assn standard single material response or ams 5732 assn standard single material response or ams 5525 assn standard single |
| material response   |
| Surface Treatment:  |
| Passivate nut   |
| Surface Treatment Specification:  |
| Qq-p-416, ty2, cl2 federal specification single treatment response washer   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Filg:   |
| A021a0  |