NSN 5310-01-352-7731

Fiig: A021a0

Double Hexagon Extended Washer Self-locking Nut - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5310-01-352-7731 |
|---|
| Thread Class: |
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Washer Outside Diameter: |
| 0.760 inches |
| Counterbore Diameter: |
| 0.474 inches first end and 0.484 inches first end |
| Lubrication: |
| Dry film lubricant |
| Overall Height: |
| Between 0.458 inches and 0.478 inches |
| Nut Style: |
| Double hexagon |
| Washer Thickness: |
| Between 0.072 inches and 0.087 inches |
| Width Across Flats: |
| Between 0.492 inches and 0.502 inches |
| Thread Series: |
| Unjf |
| Thready Qty Per Inch (tpi): |
| 24 |
| Thread Size: |
| 0.375 inches |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5737 assn standard single material response or ams 5732 assn standard single material response or ams 5525 assn standard single |
| material response |
| Surface Treatment: |
| Passivate nut |
| Surface Treatment Specification: |
| Qq-p-416, ty2, cl2 federal specification single treatment response washer |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |