NSN 5310-01-353-3638

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-353-3638 **Thread Class: Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Counterbore Diameter:** 0.372 inches first end Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 0.130 inches and 0.135 inches **Nut Style:** Plate **Nut Length:** 1.025 inches **Nut Height:** 0.828 inches **Plate Thickness:** 0.035 inches **Nut Counterbore Depth:** 0.135 inches first end **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.445 inches and 0.505 inches Center To Center Distance Between Mounting Holes Along Width: Between 0.705 inches and 0.709 inches **Thread Series:** Unif **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 24

Thread Size:

0.312 inches

Material:

Steel comp 1050 shell or steel comp 4130 shell

Material Specification:

Qq-a-225/6 federal specification single material response washer or qq-a-225/9 federal specification single material response washer

NSN 5310-01-353-3638

Plate Self-locking Nut - Page 2 of 2



Surface Treatment:
Passivate nut
Surface Treatment Specification:
Qq-p-416, ty2, cl2 federal specification single treatment response shell
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A021a0

Mil-r-25988 spec.

Mil-std (military Standard):