

View Online at <https://aerobasegroup.com/nsn/5310-01-353-3639>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Counterbore Diameter:**

0.240 inches first end

**Lubrication:**

Dry film lubricant

**Mounting Hole Diameter:**

Between 0.098 inches and 0.102 inches

**Nut Style:**

Plate

**Nut Length:**

0.786 inches

**Nut Height:**

0.640 inches

**Plate Thickness:**

0.025 inches

**Nut Counterbore Depth:**

0.125 inches first end

**Nut Mounting Provision:**

Straight holes

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

Between 0.339 inches and 0.349 inches

**Center To Center Distance Between Mounting Holes Along Width:**

Between 0.484 inches and 0.488 inches

**Thread Series:**

Unjf

**Features Provided:**

Floating nut

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Material:**

Steel comp 1050 shell or steel comp 4130 shell

**Material Specification:**

Qq-a-225/6 federal specification single material response washer or qq-a-225/9 federal specification single material response washer

**Surface Treatment:**

Passivate nut

**Surface Treatment Specification:**

Qq-p-416, ty2, cl2 federal specification single treatment response shell

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0

**Mil-std (military Standard):**

Mil-r-25988 spec.