NSN 5310-01-359-8010

Spline Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-359-8010

| view Offilite at https://aerobasegroup.com/hsr//5576-57-555-5676 |
|--|
| Thread Class: |
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Pilot Diameter: |
| 0.270 inches |
| Pilot Length: |
| 0.285 inches |
| Counterbore Diameter: |
| 0.235 inches boss |
| Lubrication: |
| Dry film lubricant |
| Nut Style: |
| Spline (floating) |
| Nut Length: |
| 0.587 inches |
| Nut Height: |
| 0.555 inches |
| Width Across Flats: |
| 0.405 inches |
| Tempurature Rating: |
| 450.0 degrees fahrenheit |
| Thread Series: |
| Unjf |
| Features Provided: |
| Floating nut |
| Thready Qty Per Inch (tpi): |
| 32 |
| Hardness Rating: |
| 49.0 rockwell c |
| Thread Size: |
| 0.190 inches |
| Material: |
| Steel comp 1050 basesteel comp 1050 nutsteel comp 304 boss or steel comp 305 boss |
| Material Specification: |
| Ams 5085 assn standard single material response baseams 5085 assn standard 1st material response nut or ams 5639 assn standard 2nd |
| material response nutams 5639 assn standard 1st material response boss or ams 5514 assn standard 2nd material response boss |
| Surface Treatment: |
| Cadmium base and chromate basecadmium nutcadmium boss and chromate boss |

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses baseqq-p-416 federal specification single treatment response nutqq-p-416, type 2 cl 2 federal specification all treatment responses boss

NSN 5310-01-359-8010

Spline Self-locking Nut - Page 2 of 2



| Shelf Life: |
|-------------------|
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |
| Fiig: |

Mil-std (military Standard):

Mil-n-25027 spec.