NSN 5310-01-362-6956



Plate Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-01-362-6956 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 0.130 inches and 0.135 inches **Nut Style:** Plate **Nut Length:** 1.292 inches **Nut Height:** 0.328 inches **Plate Thickness:** 0.045 inches Plate Width: Between 0.584 inches and 0.609 inches **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.495 inches and 0.505 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.998 inches and 1.002 inches **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unif Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches Material: Iron alloy 660

Material Specification:

Ams 5525 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single

material response

Surface Treatment:

Passivate

NSN 5310-01-362-6956

Plate Self-locking Nut - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Qq-p-35 federal specification single treatment response

Specification Data:

80205-nas1773 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0