NSN 5310-01-365-6330

Blind Rivet Plain Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-365-6330

| Thread Class: |
|--|
| 3b |
| Thread Direction: |
| Right-hand |
| Head Style: |
| Flat countersunk reverse keyed |
| Head Diameter: |
| 0.355 inches |
| Key Length: |
| 0.063 inches |
| Head Height: |
| 0.063 inches |
| Nut Style: |
| Blind rivet w/smooth round shank |
| Nut Diameter: |
| Between 0.217 inches and 0.221 inches |
| Nut Length: |
| Between 0.610 inches and 0.640 inches |
| Err Default: |
| +0.201/+0.241 inches |
| Shank End Type: |
| Open |
| Thread Series: |
| Unc |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.164 inches |
| Head Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Steel comp 430 |
| Material Specification: |
| Astm a276 assn standard single material response or astm a580 assn standard single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 2 federal specification single treatment response |
| Specification Data: |
| 80205-nas1330 professional/industrial association standard |
| Shelf Life: |

N/a

NSN 5310-01-365-6330

Blind Rivet Plain Nut - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A021a0