NSN 5310-01-373-3275

Plate Self-locking Nut - Page 1 of 2

Thread Class:

View Online at https://aerobasegroup.com/nsn/5310-01-373-3275



3b **Thread Direction: Right-hand** Locking Feature: Prevailing torque all metal design **Counterbore Diameter:** 0.195 inches first end and 0.200 inches first end Lubrication: Dry film lubricant Mounting Hole Diameter: Between 0.098 inches and 0.103 inches Nut Style: Plate Nut Length: 1.375 inches **Nut Height:** 0.750 inches **Plate Thickness:** Between 0.023 inches and 0.027 inches Plate Width: 0.865 inches Nut Counterbore Depth: 0.843 inches first end and 0.853 inches first end **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.557 inches and 0.567 inches Center To Center Distance Between Mounting Holes Along Length: Between 1.123 inches and 1.127 inches **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unif **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches

NSN 5310-01-373-3275

Plate Self-locking Nut - Page 2 of 2



Special Features:

Three shims bonded to base of shell, cres, each 0.010 in. Thk; also nut plate protrudes at one end

Material:

Steel comp 631 spring

Material Specification:

Ams 5731 assn standard single material response nut or ams 5732 assn standard single material response nut or ams 5737 assn standard

single material response nut

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A021a0