AeroBase Group

View Online at https://aerobasegroup.com/nsn/5310-01-375-7675

| Thread Class: |
|--|
| |
| 3b |
| Thread Direction: |
| |
| Locking Feature: |
| Prevailing torque all metal design |
| Washer Outside Diameter: |
| Between 0.675 inches and 0.708 inches |
| Lubrication: |
| Dry film lubricant |
| Overall Height: |
| Between 0.308 inches and 0.328 inches |
| Nut Style: |
| Hexagon |
| Washer Thickness: |
| Between 0.010 inches and 0.040 inches |
| Width Across Flats: |
| Between 0.494 inches and 0.505 inches |
| Thread Series: |
| Unjc |
| Thready Qty Per Inch (tpi): |
| 20 |
| Hardness Rating: |
| 49.0 rockwell c |
| Thread Size: |
| 0.438 inches |
| Material: |
| Steel comp 4340 or steel comp 8740 |
| Material Specification: |
| Ams 6415 assn standard 1st material response or ams 6322 assn standard 2nd material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, ty2 federal specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A021a0 |
| |
| |