NSN 5310-01-388-7956

Hexagon Extended Washer Self-locking Nut - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5310-01-388-7956 |
|--|
| Thread Class: |
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Washer Outside Diameter: |
| 0.420 inches |
| Lubrication: |
| Dry film lubricant |
| Overall Height: |
| Between 0.173 inches and 0.203 inches |
| Nut Style: |
| Slotted hexagon |
| Washer Thickness: |
| 0.020 inches |
| Width Across Flats: |
| Between 0.305 inches and 0.315 inches |
| Thread Series: |
| Unjf |
| Thready Qty Per Inch (tpi): |
| 28 |
| Thread Size: |
| 0.250 inches |
| Criticality Code Justification: |
| Feat |
| Special Features: |
| Safety critical thread per federal standard h28/20 system 22 |
| Material: |
| Steel comp 1035 or steel comp 1042 or steel comp 1137 or steel comp 4027 or steel comp 4037 or steel comp 8740 |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, ty2, cl2 federal specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A021a0