NSN 5310-01-389-2554

Spline Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-389-2554

| Thread Class: |
|--|
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Pilot Diameter: |
| 0.270 inches |
| Pilot Length: |
| 0.254 inches |
| Counterbore Diameter: |
| 0.235 inches nut |
| Lubrication: |
| Dry film lubricant |
| Nut Style: |
| Spline (floating) |
| Nut Length: |
| 0.587 inches |
| Nut Height: |
| 0.524 inches |
| Width Across Flats: |
| 0.405 inches |
| Tempurature Rating: |
| 450.0 degrees celsius |
| Thread Series: |
| Unjc |
| Features Provided: |
| Floating nut |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.164 inches |
| Material: |
| Steel comp 631 bracket |
| Material Specification: |
| Ams5639 assn standard 1st material response base or ams5514 assn standard 2nd material response base |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Shelf Life: |
| N/o |

NSN 5310-01-389-2554

Spline Self-locking Nut - Page 2 of 2



| | | | re: |
|--|--|--|-----|
| | | | |
| | | | |

--

Demilitarization:

No

Fiig:

A021a0